

Intex Acrylic Gap & Joint Sealant - White 450g

Identification of the Material & Supplier

Product Code: 6WRS
Recommended use: A general purpose, gunnable sealant for brick, concrete, masonry, timber etc.
Supplier: **Intex Group International** Pty Ltd (ACN 163012039) 115 McKellar Way Epping, Victoria, Australia 3076
+61 3 9357 9299 (or 1300 107 108 within Australia)
Intex New Zealand Pty Ltd (NZCN 7388136) 13 Mahunga Drive, Mangere Bridge, Auckland 2022, New Zealand
+64 6 377 7255 (or 0800 278 276 within New Zealand)

13 11 26 (AU Poisons Info Centre)
0800 764 766 (NZ Poisons Info Centre)

Hazards Identification

Based on available information, this material is not classified as hazardous according to criteria of NOHSC Australia. Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail.

Poisons Schedule (Aust): Not applicable

Composition

CHEMICAL ENTITY	CAS No	PROPORTION
Non-hazardous ingredients	-	100%
		100%

First Aid Measures

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

Inhalation:

Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

Skin contact:

If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. If swelling, redness, blistering or irritation occurs seek medical assistance.

Eye contact:

If in eyes wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.

Ingestion:

Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Seek medical advice.

Notes to physician:

Treat symptomatically.

Fire-Fighting Measures

Specific hazards: Non-combustible material.

Fire fighting further advice: Not combustible, however following evaporation of aqueous component residual material can burn if ignited. On burning may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

Hazchem Code: Not applicable.

Suitable extinguishing media: Not combustible, however, if material is involved in a fire use water fog (or if unavailable fine water spray), foam, dry agent (carbon dioxide, dry chemical powder).

Accidental Release Measures

Small Spills:

Wear protective equipment to prevent skin and eye contamination. Wipe up with absorbent (clean rag or paper towels). Allow absorbent to dry before disposing with normal household garbage.

Large Spills:

Wear protective equipment to prevent skin and eye contamination and the inhalation of dust. Sweep or vacuum up, but avoid generating dust. Collect and seal in properly labelled containers or drums for disposal.

Dangerous Goods -Initial Emergency Response Guide No:

Not applicable.

Intex Acrylic Gap & Joint Sealant - White 450g

Handling & Storage

- Handling:** Avoid eye contact and repeated or prolonged skin contact.
- Storage:** Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from incompatible materials described in Section 10. Keep containers closed when not in use - check regularly for spills.

Exposure Controls / Personal Protection

National occupational exposure limits:

No value assigned for this specific material by the National Occupational Health and Safety Commission (NOHSC Australia).

Biological Limit Values:

As per the "National Model Regulations for the Control of Workplace Hazardous Substances [NOHSC: 1005 (1994)]" the ingredients in this material do not have a Biological Limit Allocated.

Engineering measures: Natural ventilation should be adequate under normal use conditions.

Personal protection equipment: OVERALLS, SAFETY SHOES, SAFETY GLASSES, GLOVES.

Wear overalls, safety glasses and impervious gloves. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or reusing.

Physical & Chemical Properties

- Form / Colour / Odour:** Thick white paste with negligible odour.
- Solubility:** Dispersable in water.
- Specific Gravity (20 °C):** 1.6-1.7
- Relative Vapour Density (air=1):** N App
- Vapour Pressure (20 °C):** N App
- FlashPoint (°C):** N Av
- Flammability Limits (%):** N App
- Autoignition Temperature (°C):** N App
- Melting Point/Range (°C):** N App
- Boiling Point/Range (°C):** N App
- pH:** N App
- [Typical values only - consult specification sheet] N Av = Not available N App = Not applicable

Stability & Reactivity

- Chemical stability:** This material is thermally stable when stored and used as directed.
- Conditions to avoid:** No information available.
- Incompatible Materials:** Oxidising agents.
- Hazardous decomposition products:** Oxides of carbon and nitrogen, smoke and other toxic fumes.
- Hazardous reactions:** No information available.

Toxicological Information

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Acute Effects

- Inhalation:** Material may be irritant to mucous membranes and respiratory tract.
- Skin contact:** Repeated or prolonged skin contact may lead to irritation.
- Eye contact:** May be an eye irritant.
- Ingestion:** Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract.
- Long Term Effects:** No information available for product.
- Acute toxicity / Chronic toxicity:** No LD50 data available for the product.

Intex Acrylic Gap & Joint Sealant - White 450g

Ecological Information

Avoid contaminating waterways.

Ecotoxicity: No information available.

Persistence and degradability: No information available.

Mobility: No information available.

Disposal Considerations

Refer to State/Territory Land Waste Management Authority.

Physical And Chemical Properties

Form / Colour / Odour: Thick white paste with negligible odour.

Solubility: Dispersable in water.

Specific Gravity (20 °C): 1.6-1.7

Relative Vapour Density (air=1): N App

Vapour Pressure (20 °C): N App

FlashPoint (°C): N Av

Flammability Limits (%): N App

Autoignition Temperature (°C): N App

Melting Point/Range (°C): N App

Boiling Point/Range (°C): N App

pH: N App

(Typical values only - consult specification sheet) N Av = Not available N App = Not applicable

Transport Information

Road And Rail Transport

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail.

Marine Transport

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

Air Transport

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

Regulatory Information

Poisons Schedule (Aust): Not applicable

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

Other Information

Supplier Name: **Intex International: 91-115 Link Drive Campbellfield, Victoria, Australia 3061**
1300 107 108 (business hours). For emergency information outside normal business hours, please ring: 13 11 26 (Poisons Info Centre)

This SDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular, how to safely handle and use the product in the workplace. Since Intex International Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this SDS in the context of how the user intends to handle and use then product in the workplace. If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company. Our responsibility for the products sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available on request

End of SDS.